



LCW two needle series

High speed, Cylinder bed, Vertical axis large hook, Compound feed and walking foot, Reverse stitch, Lockstitch machines



Variety

LCW-28BL

Applications

- For sewing medium to heavy weight fabrics, leather, synthetics, canvas and various coated and laminated materials.
- Suitable for sewing tubular and curved work such as shoes boots, bags and handbags.





LCW two needle series

Features

- Semi-automatic lubrication system.
- Vertical axis large hook.
- Safety clutch prevents the hook from being damaged.
- Reverse stitching.
- 20 & 30 inches long arm models are available.

Specifications

Variety		LCW-28BL	
Number of needle		Two needle	
Max. sewing speed		1,800 s.p.m.	
Max. stitch length		1/4" (6.2 mm)	
Clearance under	by pedal	35/64" (14 mm)	
presser foot	by hand	21/64" (8.5 mm)	
Needle bar stroke		1-5/16" (33.2 mm)	
Needle(standard)		DPx17 (#22), 135x17 (#140)	
Thread		#8 (standard)	
Hook		Vertical axis hook	
Amount of lift of walking foot		7/64"-7/32" (2.7 - 5.5 mm) standard 1/8" (standard 3.2 mm)	
Thread take up lever		Slide type	
Lubrication		Semi-automatic lubrication type	
Cylinder size		3-7/64"(79 mm) dia.	
Working space		10-5/32" x 4-21/64"	
vvoiking spe	100	(258 x 110 mm)	
Motor		Clutch motor	
Net weight(Head only)		34Kg	

NOTE: (1) Speed depends on threads, materials and type of operation

Needle gauge list

Variety	Needle gauge size	
LCW-28BL	1/4"(6.4 mm), 5/16"(7.9mm), 3/8"(9.5mm), 1/2"(12.7mm), standard : 1/4"(6.4 mm)	



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi Chiba Prefecture, 273-0018, Japan

Phone: +81-47-420-3561 (Overseas dept.)

Fax: +81-47-420-3560

E-mail: export@seiko-sewing.co.jp

Printed in Japan 2015.08	Printed in Japan 2015.08

http://www.seiko-sewing.co.jp/

⁽²⁾ Specifications subject to change without notice